

AC011E-01

11kW AC-Charger for electric vehicles

NEW



RELIABLE AND VERSATILE

- Compatible with Sungrow 3-phase Solution or as a stand-alone product
- Type2 charging plug - compatible with standard electric vehicles
- Integrated 6mA DC fault detection



USER FRIENDLY

- RFID access control with 2 cards included
- Premounted 7 m Type 2 charging cable
- Space-saving dimensions for wall mounting or optional pole-mounting



SMART AND EASY MANAGEMENT

- Control and visualization via iSolarCloud
- Controlled and managed via APP or external EMS
- Capable for OCPP 1.6 communication



SUSTAINABLE

- Beyond charging - for maximum usage of solar energy together with Sungrow 3-phase Solution
- Different charging modes to fit all needs

Type designation	AC011E-01
AC Input and Output	
Max. charge power	11 kW
Nominal Voltage	400 V
Nominal grid frequency	50 / 60 Hz
Max. current	16 A three-phase
Charge connector	Plug Type 2
Cable cross-section	5*2.5 mm ²
Cable Length	7 m
Protection Devices	
Integrated DC fault detection	6mA DC
Over/Under voltage protection	Yes
Over load protection	Yes
Over temperature protection	Yes
Surge protection	II
Overvoltage category	III (grid) / II (car)
General Data	
Dimensions (W*H*D)	205*310*92 mm
Weight	3.8 kg
Mounting method	Wall-Mounting/Pole-Mounting (optional)
Degree of protection	IP65
Operating ambient temperature range	-30 to 50 °C
Allowable relative humidity range (non-condensing)	5 % to 95 %
Cooling method	Natural convection
Max. operating altitude	2000 m
Grid type	TN/TT
Display	LED indicator
Monitoring	iSolarCloud App (with Sungrow inverter), iEnergyCharge App
Communication	RS485/WLAN
Charging protocol	OCPP 1.6
Power consumption for standby	< 5 W
Start Mode	RFID card/APP
Standard compliance	EN/IEC 61851-1:2019; IEC 61851-21-2:2018
Warranty	2.5 years (standard), 5 years (optional)